

### **Highly organized**

Systemizing more voice recorders even while recording different signal sources.

### **Centralized archiving**

Archiving all recorded data from every recorder in one centralized location.

### **High capacity**

Stores up to 432.000 hours of speech that can be accessed on-line.

### **Authorizing system**

Provides multi-level access rights to all authorized personnel in one centralized system.

### **Highly flexible**

System services and upgrades according to type and license.

### **Service and support**

Quick and effective service, technical interface and full circle factory support.

DSR Ltd. has developed SLDCenter archiving, servicing and system administering center to accomplish increased safety, storage capacity, handling and archiving comfort and higher level of integrity.

The main tasks of SLDCenter are to link digital voice recorders and to archive all recorded conversations and related data in its high capacity built-in storage. The end product of this activity is a modern database with all record-information and an on-line accessible records-file with more hundreds of thousands of records. Records from here can be copied to an external media. Using SLDCenter, the centrally archived records can be copied to a user selected high capacity mass storage device in order to long term preservation. The system completely administers copying processes as well as other events.

SLDCenter provides a private user interface to be able to access the recorded, documented and archived records and provides supervised links for all connected devices (recorders, client workstations).

### **Key Properties**

- TCP / IP connection with DSR SoliDBank<sup>®</sup> digital voice recorders.
- Storing and on-demand archiving every conversation and related data in a centralized location.
- Optional simultaneous replaying of records for more users.
- Archiving to mobile media (e.g. DVD) and/or high capacity mass storage (NAS, SAN).
- Access to archives according to pre-defined authorizing rights.
- Providing homogenous system time to every digital voice recorder of the system.
- System processes can be scheduled – database update, archiving, user services.
- Providing the remote management of the whole system through a web interface.

### Technical Data Sheet

Handling of SLDCenter is performed by proprietary software, the help of which all functions of the device can be accessed from a central location. The operating system and other additional software installed on the SLDCenter manage the central database building and archiving; and handle access rights. The software manages system administration and time synchronizing. The application also serves remote user and client-accesses on the basis of the central authorization system.

<b>Basic parameters</b>	
<b>Number of voice recorders to be connected</b>	1-12
<b>Maximum storage capacity</b>	20.000 hours
<b>Number of registered users</b>	5
<b>Number of channels can be archived</b>	120
<b>Number of records to be handled and stored</b>	max. 1 million
<b>Operating system</b>	MS Windows XP Prof.

<b>Extension options</b>	
<b>RAID</b>	RAID1 level data security
<b>T20</b>	extension of storage capacity to 400.000 hours
<b>U10</b>	extension of registered users to 10
<b>U15</b>	extension of registered users to 15
<b>U20</b>	extension of registered users to 20
<b>UL</b>	unlimited license (maximum nr. of users: 256)
<b>SD</b>	building selective database
<b>SA</b>	selective archiving

<b>Technical data</b>	
<b>POWER SUPPLY</b>	100-240 V AC, 9-7A, 47-63 Hz
<b>POWER CONSUMPTION</b>	110 – 200 W
<b>DIMENSIONS</b>	19" rackable, 2U high, 500 mm deep
<b>TEMPERATURE</b>	operating: +5...+50 °C / storage: -30...+60 °C
<b>HUMIDITY</b>	operating: 10...90 % RH / storage: 5...95 % RH
<b>CHANGE OF TEMPERATURE</b>	operating: max. 20 °C/hour / storage: max. 30 °C/hour
<b>OPERATING CONDITIONS</b>	air-conditioned environment is recommended