

# SolidBank® 601 Compact E1

## Digital voice recorder

for ISDN30 (E1) lines



<b>Automatic operation</b>	Automatically records communication.
<b>Lots of data</b>	Up to 20.800 hours of data, depending on compression.
<b>Remote management</b>	Status and error signals are accessible via a web interface.
<b>Alarm</b>	SNMP capability.
<b>Authorizing system</b>	Multi level system with protection against unauthorised access.
<b>Logging</b>	Logs functions and user actions.
<b>Service and support</b>	Quick and efficient service as well as complete factory support.
<b>Easy archiving</b>	By using SLDCenter.



From small- and medium-sized enterprises to big companies, from private sector and public organizations to armed forces and special services - now everyone can find the optimal digital voice recorder for their needs in the **SolidBank® 601** product family.

By utilizing the members of the product family, recording and retrieving transactions are simple and effective. The unique, non PC-based set-top box-type hardware and its software elements provide the maximum safety for all recorded data. All information hidden in calls is saved for the long-term; it can be replayed any time and can be used for any purpose from recording essential business data, to collecting marketing information or improving the quality of your workflow.

If required, complex SoliDLog® systems can be constructed by linking several voice recorders. For these systems we provide archiving and improved data-storage solutions. **SolidBank® 601 Compact E1** has been developed for recording communication through ISDN30 lines.



### Recording

**Flexible configuration** - you can record the voice communication of 30 (1 ISDN30 (E1) trunk) channels maximum.

**Several startups** - automatic startup at off-hook, signal-level or contact. The recorder can start and stop recording by evaluating digital signals and is able to receive CTI orders.

**Voice documenting** - storing additional data besides records, by which important information is recoverable and it is easier to retrieve certain conversations.

**Compression** - in cases of increased data flow the compress option can be employed to store eight times more data on the same storage place. Downloading time decreases when replaying compressed data.



### Replaying

**Accessibility** - recorded calls and call-information can be accessed and managed by using a client-application or through the web by using a common browser.

**Flexible search** - by using the stored additional information it is possible to implement aimed search and with the help of specified parameters recordings can be filtered and listed as well. Filter conditions can be combined on demand to assist aimed search.

**Exporting** - after taking safety issues into consideration recorded data can be saved in several formats, enclosed and sent as an attachment; or published on the web.

**Safety** - this multi-level, flexible authorizing system can prevent unauthorized access. Every user is permitted to accomplish only pre-determined working processes.

# SoliDBank® 601 Compact E1

## Digital voice recorder

for ISDN30 (E1) lines



### Voice recording specification

Simultaneously recordable channels	max. 30
Recordable sources	ISDN30 (E1) (DSS1, QSIG)
Startup	<ul style="list-style-type: none"><li>• ISDN inputs: contact and on-hook ( based on D-channel signals)</li><li>• Ethernet: command over CTI</li></ul>
Storage media	mirrorable 2,5" HDD*
Storage format (configurable per channel)	uncompressed: G.711 A-Law PCM (64 Kbit/s); compressed: Speex SPX (8 Kbit/s)
Storage capacity	uncompressed: max. 2.600 h; compressed: max. 20.800 h
Listing, replaying	10/100BASE-T Ethernet <ul style="list-style-type: none"><li>• web interface client application, Internet browser</li><li>• DSR EasyReplay application</li></ul>
Auxiliary information to help retrieving	<ul style="list-style-type: none"><li>• phone number of extension and remote party</li><li>• call direction</li><li>• identifier of agent and client</li><li>• starting time and length of record</li><li>• channel identifier</li><li>• source of call transfer</li><li>• textual comment</li></ul>
Saving records to workstation	<ul style="list-style-type: none"><li>• by using a browser</li><li>• by using DSR EasyReplay client</li></ul>
Alarm	<ul style="list-style-type: none"><li>• alarm LED</li><li>• via the web interface</li><li>• via SNMP</li></ul>

\* In case of C4 compression, mirrorable HDD is not applicable

### Technical data

Ethernet port	10/100 Base-T (RJ45) for management over network, service
Serial port	RS232 (9 pole DSUB) for maintenance functions
Power	100-240 V AC, 1.5A, 50-60 Hz, or 48 V DC
Power consumption	max. 35 W (depending on build)
Mechanical finish	compact , desktop finish
Dimensions	285 mm wide, 85 mm high, 220 mm deep
Temperature	operating: +10...+40 °C / storage: -30...+60 °C
Humidity	operating : 10...90 % RH / storage : 5...95 % RH
Changes of temperature	operating: max. 20 °C/h / storage: max. 30 °C/h
Input connector	RJ45 connector (120 Ohm symmetric)



Office: H-1117 Budapest, Prielle Kornélia u. 19/G

Tel.: +36 1 464 4380 • Fax: +36 1 371 1788 • e-mail: support@dsr.hu



[www.dsr.hu](http://www.dsr.hu)

DSR Ltd. reserves the right to make modifications.