

Automatic operation

Automatically records communication.

Lots of data

Up to 62.500 hours of data, depending on compression.

Remote management

Status and error signals are accessible via a web interface.

Alarm

SNMP capability.

Authorizing system

Multi level system with protection against unauthorized access.

Logging

Logs functions and user actions.

Service and support

Quick and efficient service as well as complete factory support.

Easy archiving

By using the optional FTP client.

From small- and medium-sized enterprises to big companies, from private sector and public organizations to armed forces and special services, now everyone can find the optimal digital voice recorder for their needs in the SoliDBank[®] 601 product family.

By utilizing the members of the product family, recording and retrieving transactions are simple and effective. The unique hardware and software elements provide the maximum safety for all recorded data. All information hidden in calls is saved for the long-term; it can be replayed any time and can be used for any purpose from recording essential business data, to collecting marketing information or improving the quality of your workflow.

If required, complex SoliDLog[®] systems can be constructed by linking several voice recorders. For these systems we provide archiving and improved data-storage solutions.

SoliDBank[®] 601 Flat VoIP 200 has been developed for recording Voice over IP signal sources from virtually all PBXs using port-mirroring technology.

Recording

Large capacity - recording up to 200 VoIP voice channels in one device. Number of channels can be extended in singles by purchasing the required channel license.

Voice documenting - storing additional data besides records, by which important information is recoverable and it is easier to retrieve certain conversations.

Data format - the device is ready to record the most popular data formats. The largest amount of data can be stored in G.723, and it also provides the shortest download time when retrieving.

Replaying

Accessibility - recorded calls and call-information can be accessed and managed by using a client-application or through the web by using a common browser.

Flexible search - by using the stored additional information, it is possible to implement aimed search and with the help of specified parameters recordings can be filtered and listed as well. Filter conditions can be combined on demand to assist aimed search.

Exporting - after taking safety issues into consideration recorded data can be saved in several formats, enclosed and sent as an attachment; or published on the web.

Safety - this multi-level, flexible authorizing system can prevent unauthorized access. Every user is permitted to accomplish only pre-determined working processes.

Voice recording specification	
Simultaneously recordable channels	<ul style="list-style-type: none"> max. 200 (depending on the license)
Recordable signal sources	<ul style="list-style-type: none"> Cisco (Skinny) Avaya (H.323) Alcatel-Lucent (H.323) Ericsson (H.323) Panasonic (H.323) Siemens (CorNet IP) Nortel (H.323) Asterisk (SIP)
Startup	<ul style="list-style-type: none"> automatic
Storage media	<ul style="list-style-type: none"> 3,5" HDD
Format of storage	<ul style="list-style-type: none"> G.711 A-Law PCM (uncompressed, 2 x 64 Kbit/s) G.723 (compressed, 2 x 6,3 kbit/s) G.729, G.729A (compressed, 2 x 8 Kbit/s)
Storage capacity	<ul style="list-style-type: none"> G711 (uncompressed): max. 6.250 h G723 (compressed): max. 62.500 h G729, G.729A (compressed): max. 50.000 h
Listing, replaying	Gigabit Ethernet: <ul style="list-style-type: none"> web interface client application, Internet browser DSR EasyReplay application
Auxiliary information to help retrieving	<ul style="list-style-type: none"> starting time length of call phone number of caller and called name associated to extension call direction coding
Save records to workstation	<ul style="list-style-type: none"> by using a browser by using DSR EasyReplay client
Alarm	<ul style="list-style-type: none"> via the web interface via SNMP

Technical data	
Power	100-240 V AC, 6-3A, 47-63 Hz
Power consumption	max. 160 W
Dimensions	19" rackable, 2U high, 500 mm deep
Temperature	operating: +5...+50 °C / storage: -30...+60 °C
Humidity	operating: 10...90 % RH / storage: 5...95 % RH
Change of temperature	operating: max. 20 °C/h / storage: max. 30 °C/h