



**Factory solution**

AVAYA Compliance Tested.

**Automatic operation**

Automatically records communication.

**Lots of data**

Up to 62.500 hours of online accessible data, depending on compression.

**Remote management**

Status and error signals are accessible via a web interface.

**Alarm**

SNMP capability.

**Authorizing system**

Multilevel system with protection against unauthorized access.

**Logging**

Logs functions and user actions.

**Service and support**

Quick and efficient service as well as complete factory support.

**Easy archiving**

By using the optional FTP client.

From small- and medium-sized enterprises to big companies, from private sector and public organizations to armed forces and special services, now everyone can find the optimal digital voice recorder for their needs in the SoliDBank<sup>®</sup> 601 product family.

By utilizing the members of the product family, recording and retrieving transactions are simple and effective. The unique hardware and software elements provide the maximum safety for all recorded data. All information hidden in calls is saved for the long-term; it can be replayed any time and can be used for any purpose from recording essential business data, to collecting marketing information or improving the quality of your workflow.

If required, complex SoliDLog<sup>®</sup> systems can be constructed by linking several voice recorders. For these systems we provide archiving and improved data-storage solutions. SoliDBank<sup>®</sup> 601 AVAYA VoIP 100 is the youngest member of the product family and has been developed for recording Voice over IP signal sources on AVAYA DMCC-API.

## **Recording**

*UP-to-date interfaces* - it is possible to record via the AVAYA supported and tested DMCC-API interface.

*Large capacity* - recording up to 100 VoIP voice channels in one device. Number of channels can be extended in singles by purchasing the required channel license.

*Voice documenting* - storing additional data besides records, by which important information is recoverable and it is easier to retrieve certain conversations.

*FTP archiving* - the device is capable of utilizing an existing FTP connection to archive the recorded data onto any backup storage (NAS, SAN, etc.). This feature saves reasonable amounts of money to all who need a simple archiving solution.

## **Replaying**

*Accessibility* - recorded calls and call-information can be accessed and managed by using a client-application or through the web by using a common browser.

*Flexible search* - by using the stored additional information, it is possible to implement aimed search and with the help of specified parameters recordings can be filtered and listed as well. Filter conditions can be combined on demand to assist aimed search.

*Exporting* - after taking safety issues into consideration recorded data can be saved in several formats, enclosed and sent as an attachment; or published on the web.

*Safety* - the multi-level, flexible authorizing system can prevent unauthorized access. Every user is permitted to accomplish only pre-determined working processes.

<b>Voice recording specification</b>	
<b>Simultaneously recordable channels</b>	<ul style="list-style-type: none"> <li>max. 100 (depending on the license)</li> </ul>
<b>Recordable signal sources</b>	<ul style="list-style-type: none"> <li>Avaya DMCC-API (Communication Manager 5.1, AES 4.2)</li> </ul>
<b>Startup</b>	<ul style="list-style-type: none"> <li>automatic</li> </ul>
<b>Storage media</b>	<ul style="list-style-type: none"> <li>3,5" HDD</li> </ul>
<b>Format of storage</b>	<ul style="list-style-type: none"> <li>G.711 (uncompressed)</li> <li>G.723 (compressed 2x6,3 Kbit/s)</li> <li>G.729, G.729A (compressed, 2 x 8 Kbit/s)</li> </ul>
<b>Storage capacity</b>	<ul style="list-style-type: none"> <li>G.711 (uncompressed): 6.250 h</li> <li>G.723 (compressed): 62.500 h</li> <li>G.729, G.729A ( compressed ): 50.000 h</li> </ul>
<b>Listing, replaying</b>	Gigabit Ethernet: <ul style="list-style-type: none"> <li>web interface client application, Internet browser</li> <li>DSR EasyReplay application</li> </ul>
<b>Auxiliary information to help retrieving</b>	<ul style="list-style-type: none"> <li>starting time</li> <li>length of call</li> <li>phone number of caller and called</li> <li>name associated to extension</li> <li>call direction</li> <li>coding</li> <li>caller agent ID</li> <li>UCID</li> </ul>
<b>Save records to workstation</b>	<ul style="list-style-type: none"> <li>by using a browser</li> <li>by using DSR EasyReplay client</li> </ul>
<b>Alarm</b>	<ul style="list-style-type: none"> <li>via the web interface</li> <li>via SNMP</li> </ul>

<b>Technical data</b>	
<b>Power</b>	100-240 V AC, 6-3A, 47-63 Hz
<b>Power consumption</b>	max. 160 W
<b>Dimensions</b>	19" rackable, 2U high, 500 mm deep
<b>Temperature</b>	operating: +5...+50 °C / storage: -30...+60 °C
<b>Humidity</b>	operating: 10...90 % RH / storage: 5...95 % RH
<b>Change of temperature</b>	operating: max. 20 °C/h / storage: max. 30 °C/h